SR5600
External RAID Subsystem

Key Features
- RAID subsystem with power supply
- 4x 3.5" SATA HDD
- Aluminium housing
- RAID Level RAID 0, 1, 1+0,
- Host interface:
  USB 2.0 + 1394b, USB 2.0 + eSATA
- Online Auto Rebuilding (RAID 1)
- Plug & Play, Hot swappable
- LCD Display
- OS independent
- Alarm on overheating, fan or HDD failure

Content:
- Com to HTTP Software
- Power cord
- RS 232 cable
- data cable

Data security through real time mirroring control by display or RAIDGuide software. USB 2.0 + 1394b, USB 2.0 + eSATA host interface

Technical Data		
Model	**SR 5600-4S-WBC**	**SR 5600-4S-SB2**
Art.-No.	12039	12084
Colour	Silver/black	Silver/black
RAID Level	0,1,(0+1), RAID	0,1,(0+1), RAID
Host Interface	1394b + USB 2.0	USB 2.0 + eSATA
HDD Interface	4x 3.5" SATA	4x 3.5" SATA
Auto rebuilding	Yes	Yes
Cooling Fan	1x 60 mm	1x 60 mm
Power supply	200 W A/C Input 100~230 V, 50-60 Hz	

Logistic Data

Packing unit:	8 pcs./carton	**Gross weight:**	5.7 kg	**Import tax:**	84733090
Total weight:	24.0 kg	**Dimension (with packing):**	395 x 190 x 228 mm		
Dimension/carton:	412 x 408 x 486 mm	**Net weight:**	5.2 kg		
Dimension of article:	270 x 147 x 115mm	**Country of origin:**	Taiwan		

RaidSonic Technology GmbH • Kurt-Fischer-Straße 50 • 22926 Ahrensburg / Germany
Telefon: +49-(0)4102-468900 • Fax: +49-(0) 4102-468901 • www.raidsonic.de
Errors excepted. All data subject to change without notice.

RaidSonic
STORAGE SOLUTIONS WITHOUT LIMITS